



INTERCHANGEABILITY LIST

PRESSURE SWITCHES

DUNGS - SUNTEC

	DUNGS	SUNTEC	REMARKS	
DMG range			Pressure range	Specifications
	GW 3 A5	DMG 003	SUNTEC (0.7 - 3 mbar) DUNGS (1 - 3 mbar)	Max. operating pressure : SUNTEC : 690 mbar DUNGS : 500 mbar
	GW 10 A5	DMG 010		
	GW 50 A5	DMG 050	SUNTEC (2.5 - 50 mbar) DUNGS (5 - 50 mbar)	Dimensions : SUNTEC : 96.8 x 48.5 x 49.5 mm DUNGS : 72 x 55.5 x 44.7 mm
GW 150 A5	DMG 150			
F range	GW 3 A6	FCG 003/FSG 003	SUNTEC (0.7 - 3 mbar) DUNGS (1 - 3 mbar)	Max. operating pressure : SUNTEC : 690 mbar DUNGS : 500 mbar (600mbar for GW 500)
	GW 10 A6	FCG 010/FSG 010		
	GW 50 A6	FCG 050/FSG 050	SUNTEC FCG 050 (2.5 - 50 mbar) DUNGS (5 - 50 mbar)	Dimensions : SUNTEC : 96.8 x 49.3 x 60.5 mm DUNGS : 72 x 42 x 58.4 mm
	GW 150 A6	FCG 150/FSG 150		
	GW 500 A6	FCG 500		

SIEMENS - SUNTEC

	SIEMENS	SUNTEC	REMARKS	
DMG range			Pressure range	Specifications
	QPL15.050	DMG 050	SUNTEC (2.5 - 50 mbar) SIEMENS (5 - 50 mbar)	Same max. operating pressure Same dimensions
	QPL15.150	DMG 150		
F range	QPL25.003	FCG 003/FSG 003		
	QPL25.010	FCG 010/FSG 010		
	QPL25.050	FCG 050/FSG 050	SUNTEC (2.5 - 50 mbar) SIEMENS (5 - 50 mbar)	
	QPL25.150	FCG 150/FSG 150		
	QPL25.500	FCG 500		

INTERCHANGEABILITY LIST

SHINEUI - SUNTEC

	SHINEUI	SUNTEC	REMARKS	
F range			Pressure range	Operational
	SGPS 3V	FCG 003/FSG 003	SUNTEC (0.7 - 3 mbar) SHINEUI (0.4 - 3 mbar)	Max. operating pressure : SUNTEC : 690 mbar SHINEUI : 500 mbar Dimensions : SUNTEC : 96.8 x 49.3 x 60.5 mm SHINEUI : 72 x 72 x 56.5 mm
	SGPS 10V	FCG 010/FSG 010		
	SGPS 50V	FCG 050/FSG 050	SUNTEC FSG 050 (5 - 50 mbar) SHINEUI (2.5 - 50 mbar)	
	SGPS 150V	FCG 150/FSG 150	SUNTEC (5 - 150 mbar) SHINEUI (30 - 150 mbar)	
SGPS 500V	FCG 500			

KROMSCHRÖDER - SUNTEC

	KROMSCHRÖDER	SUNTEC	REMARKS	
F range			Pressure range	Operational
	DG 6B	FCG 003/FSG 003	SUNTEC (0.7 - 3 mbar) KROMSCHRÖDER (0.5 - 6 mbar)	Max. operating pressure : SUNTEC : 690 mbar KROMSCHRÖDER : 600 mbar Dimensions : SUNTEC : 96.8 x 49.3 x 60.5 mm KROMSCHRÖDER : 76 x 76 x 50 mm
	DG 10B	FCG 010/FSG 010	SUNTEC (2 - 10 mbar) KROMSCHRÖDER (1 - 10 mbar)	
	DG 50B	FCG 050/FSG 050	SUNTEC FSG 050 (5 - 50 mbar) KROMSCHRÖDER (2.5 - 50 mbar)	
	DG 150B	FCG 150/FSG 150	SUNTEC (5 - 150 mbar) KROMSCHRÖDER (30 - 150 mbar)	
DG 500B	FCG 500			